

Printing date 18.12.2019 Revision: 18.12.2019 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: Aerosol Isoliergrundierung weiss • Article number (product ID.): REZ764 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Application of the substance / the mixture: painting · Uses advised against No further relevant information available. \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Peter Kwasny GmbH Heilbronner Str. 96 D-74831 Gundelsheim Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de · Further information obtainable from: Product safety department · 1.4 Emergency telephone number: Tel.:+49 6269 95 20 · national: National Poisons Information Service, Birmingham Tel.: 844 892 0111 · K-Nr. 0001 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1 GHS07 H315 Causes skin irritation. Skin Irrit. 2 STOT SE 3 May cause drowsiness or dizziness. H336 H304 May be fatal if swallowed and enters airways. Asp. Tox. 1 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger

Page 1/9

Printing date 18.12.2019

Revision: 18.12.2019

	(Contd. of page 1
· Hazard-a	determining components of labelling:
EC921-0	24-6 Naphtha (petroleum), hydrotreated light
EC927-2	41-2 Naphtha (petroleum), hydrotreated light
EC920-7	50-0 Naphtha (petroleum), hydrodesulfurized heavy
ethylbenz	zene
· Hazard s	tatements
H222-H2	229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
· Precauti	onary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P302+P.	352 IF ON SKIN: Wash with plenty of water.
P312	Call a POISON CENTER/doctor if you feel unwell.
	313 If skin irritation occurs: Get medical advice/attention.
P410+P4	412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

	EC921-024-6 Naphtha (petroleum), hydrotreated light	10-<25%
Reg.nr.: 01-2119475514-35-xxxx	� Flam. Liq. 2, H225; � Asp. Tox. 1, H304; � Aquatic Chronic 2, H411; � Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 115-10-6	dimethyl ether	10-<25%
EINECS: 204-065-8	🚸 Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119472128-37-xxxx		
CAS: 74-98-6	propane	10-<25%
EINECS: 200-827-9	🚸 Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119486944-21-xxxx		
	EC927-241-2 Naphtha (petroleum), hydrotreated light	10-<25%
Reg.nr.: 01-2119471843-32-xxxx	Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412	
CAS: 106-97-8	butane (containing $\leq 0,1$ % butadiene (203-450-8))	10-<25%
EINECS: 203-448-7	🚸 Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119474691-32-xxxx		
	(Col	ntd. on page

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol Isoliergrundierung weiss

CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing $\leq 0,1$ % butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas C, H280	Contd. of page 2) 5-<10%
CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35-xxxx		1-<2.5%
· Additional information: For the	wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling
- Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol Isoliergrundierung weiss

(Contd. of page 3)

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, *i.e. electric lights. Do not pierce or burn, even after use.*

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: None.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

7727-43-7 barium sulphate, natural

WEL Long-term value: 10* 4** mg/m³

*inhalable dust **respirable dust

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- · Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Protection of hands:

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

(Contd. on page 5)

GI

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol Isoliergrundierung weiss

(Contd. of page 4)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

 \cdot For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

• Eye protection: Not required.

· Partition coefficient: n-octanol/water:

· Viscosity: Dynamic:

Kinematic:

· Solvent content:

Organic solvents:

SECTION 9: Physical and chemical properties · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Aerosol Colour: According to product specification · Odour: *Characteristic* · Odour threshold: Not determined. Not determined. · pH-value: · Change in condition Melting point/freezing point: Undetermined. Initial boiling point and boiling range: -44.5 °C <0 °C · Flash point: Without propellant gas. · Flammability (solid, gas): Not applicable. 235 °C · Ignition temperature: Not determined. · Decomposition temperature: · Auto-ignition temperature: Product is not selfigniting. Product is not explosive. However, formation of explosive air/ · Explosive properties: vapour mixtures are possible. Not determined. · Explosion limits: 1.5 Vol % Lower: 18.6 Vol % Upper: 3,600 hPa • Vapour pressure at 20 °C: Not determined. · Density: Not determined. · Relative density · Vapour density Not determined. · Evaporation rate Not applicable. · Solubility in / Miscibility with Not miscible or difficult to mix. water:

Not determined.

Not determined.

Not determined.

With propellant gas. Content given by weight.

75.4 %

(Contd. on page 6)

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol Isoliergrundie	rung weiss	
VOC (EU)	75.35 %	(Contd. of page 5)
Solids content:	24.7 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

 \cdot 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h >89.6 mg/l (rat)

· Primary irritant effect:

- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- *Carcinogenicity* Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

• 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

· Ecotoxical effects:

- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

(Contd. on page 7)

^{· 10.2} Chemical stability

GB

Printing date 18.12.2019

Revision: 18.12.2019

Trade name: Aerosol Isoliergrundierung weiss

(Contd. of page 6)

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Ikke relevant.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

*

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
·ADR	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
· Class	2.1
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void not classified
· 14.5 Environmental hazards:	
• Marine pollutant:	No
 14.6 Special precautions for user Danger code (Kemler): 	Warning: Gases. - not classified
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.
-	SW22 For AEROSOLS with a maximum capacity of 1 litre:
	(Contd. on page 8)

GB

Printing date 18.12.2019

Revision: 18.12.2019


Trade name: Aerosol Isoliergrundierung weiss (Contd. of page 7) Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: · Segregation Code Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1LCode: E0 \cdot Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category 2 • Tunnel restriction code D · IMDG lL \cdot Limited quantities (LQ) · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

· Technical instructions (air):



- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• *Relevant phrases* H220 Extremely flammable gas.

(Contd. on page 9)

⁻ GB

Printing date 18.12.2019

Revision: 18.12.2019

ide n	de name: Aerosol Isoliergrundierung weiss	
	(Contd. of page	
H2	25 Highly flammable liquid and vapour.	
	80 Contains gas under pressure; may explode if heated.	
	04 May be fatal if swallowed and enters airways.	
	15 Causes skin irritation.	
	36 May cause drowsiness or dizziness.	
	11 Toxic to aquatic life with long lasting effects.	
H4	12 Harmful to aquatic life with long lasting effects.	
· Der	partment issuing SDS: Product safety department	
-	breviations and acronyms:	
	R: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Internation	
	riage of Dangerous Goods by Road)	
IML	DG: International Maritime Code for Dangerous Goods	
	A: International Air Transport Association	
	S: Globally Harmonised System of Classification and Labelling of Chemicals	
	ECS: European Inventory of Existing Commercial Chemical Substances	
	NCS: European List of Notified Chemical Substances	
	S: Chemical Abstracts Service (division of the American Chemical Society) 50: Lethal concentration, 50 percent	
	50: Lethal dose, 50 percent	
	<i>E: Persistent, Bioaccumulative and Toxic</i>	
	B: very Persistent and very Bioaccumulative	
	m. Gas 1: Flammable gases – Category 1	
Aero	osol 1: Aerosols – Category 1	
	ss. Gas C: Gases under pressure – Compressed gas	
	m. Liq. 2: Flammable liquids – Category 2	
	1 Irrit. 2: Skin corrosion/irritation – Category 2	
	DT SE 3: Specific target organ toxicity (single exposure) – Category 3	
	. Tox. 1: Aspiration hazard – Category 1	
	atic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 atic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
	Data compared to the previous version altered.	