

Printing date 08.02.2021

Safety data sheet according to 1907/2006/EC, Article 31

	ION 1: Identification of the substance/mi	<i>v i v</i> 8
· 1.1 Pro	duct identifier	
· Trade n	ame: <u>Aerosol PU Wasserlack Klarlack mattiert</u>	
	number) product ID.: REZ1007 evant identified uses of the substance or mixture of	and uses advised against
	tion of the substance / the mixture: painting vised against No further relevant information avail	ilable.
• Manufo Peter K Heilbro	ails of the supplier of the safety data sheet acturer/Supplier: wasny GmbH nner Str. 96 1 Gundelsheim	Tel.: 0049-(0)6269-95 E-mail: labor@kwasny
· Further	information obtainable from: Product safety dep	
	ergency telephone number: Tel.:+49 6269 95 20	
• nationa		
Nationa	l Poisons Information Service, Birmingham	
Tel.: 84 • K-Nr. 0	4 892 0111	
SECT	ION 2: Hazards identification	
	ssification of the substance or mixture cation according to Regulation (EC) No 1272/200 flame	08
· Classifi Aerosol · 2.2 Lab · Labellin The pro	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements 1g according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL	essurised container: May burst if heated.
· Classifi Aerosol · 2.2 Lab · Labellin The pro	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ng according to Regulation (EC) No 1272/2008	essurised container: May burst if heated.
· Classifi Aerosol · 2.2 Lab · Labellin The pro	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements 1g according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL	essurised container: May burst if heated.
• Classifi Aerosol • 2.2 Lab • Labellin The pro	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements 1g according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL	essurised container: May burst if heated.
• Classifi Aerosol • 2.2 Lab • Labellin The pro	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ng according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms	essurised container: May burst if heated.
 Classifi Aerosol 2.2 Lab Labellin The pro Hazard GHS0 	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ng according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms	essurised container: May burst if heated.
 Classifi Aerosol 2.2 Lab Labellin The pro Hazard GHS0 Signal 	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ng according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms	essurised container: May burst if heated.
 Classifi Aerosol 2.2 Lab Labellin The pro Hazard GHS0 Signal Hazard 	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ng according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms 2 word Danger	essurised container: May burst if heated. P regulation.
 Classifi Aerosol 2.2 Lab Labellin The pro Hazard GHS0 Signal Hazard Hazard Precause 	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ng according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms 2 vord Danger statements [229 Extremely flammable aerosol. Pressurised con- tionary statements	essurised container: May burst if heated. P regulation. ntainer: May burst if heated.
 Classifi Aerosol 2.2 Lab Labellin The pro Hazard GHS0 Signal Hazard Hazard H222-E Precaus P101 	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ng according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms vord Danger statements 1229 Extremely flammable aerosol. Pressurised con- tionary statements If medical advice is needed, have product cor	essurised container: May burst if heated. P regulation. ntainer: May burst if heated.
 Classifi Aerosol 2.2 Lab Labellin The pro Hazard GHS0 Signal Hazard Hazard H222-F Precaus P101 P102 	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ig according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms vord Danger statements 1229 Extremely flammable aerosol. Pressurised con ionary statements If medical advice is needed, have product cor Keep out of reach of children.	essurised container: May burst if heated. P regulation. ntainer: May burst if heated.
 Classifi Aerosol 2.2 Lab Labellin The prod Hazard GHS0 Signal Hazard Hazard Precaute P101 P102 P103 	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ig according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms 2 vord Danger statements 1229 Extremely flammable aerosol. Pressurised con- tionary statements If medical advice is needed, have product cor Keep out of reach of children. Read carefully and follow all instructions.	essurised container: May burst if heated. P regulation. ntainer: May burst if heated. ntainer or label at hand.
 Classifi Aerosol 2.2 Lab Labellin The pro Hazard GHS0 Signal Hazard Hazard H222-F Precaus P101 P102 	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ig according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms 2 vord Danger statements 1229 Extremely flammable aerosol. Pressurised con- tionary statements If medical advice is needed, have product cor Keep out of reach of children. Read carefully and follow all instructions.	essurised container: May burst if heated. P regulation. ntainer: May burst if heated. ntainer or label at hand. pen flames and other ignition sources. No smokin
 Classifi Aerosol 2.2 Lab Labellin The pro Hazard GHS0 Signal Hazard Hazard Precau P101 P102 P103 P210 P211 P251 	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ng according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms 2 2 word Danger statements 1229 Extremely flammable aerosol. Pressurised con- ionary statements 1229 Extremely flammable aerosol. Pressurised con- ionary statements 15 medical advice is needed, have product con- Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat, hot surfaces, sparks, of Do not spray on an open flame or other ignith Do not pierce or burn, even after use.	essurised container: May burst if heated. P regulation. ntainer: May burst if heated. ntainer or label at hand. pen flames and other ignition sources. No smokir ion source.
 Classifi Aerosol 2.2 Lab Labellin The pro Hazard GHS0 Signal Hazard Hazard Precau P101 P102 P103 P210 P211 P251 	cation according to Regulation (EC) No 1272/200 flame 1 H222-H229 Extremely flammable aerosol. Pre el elements ng according to Regulation (EC) No 1272/2008 duct is classified and labelled according to the CL pictograms 2 word Danger statements 1229 Extremely flammable aerosol. Pressurised con- ionary statements 1229 Extremely flammable aerosol. Pressurised con- ionary statements If medical advice is needed, have product con- Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat, hot surfaces, sparks, of Do not spray on an open flame or other ignitic	essurised container: May burst if heated. P regulation. ntainer: May burst if heated. ntainer or label at hand. pen flames and other ignition sources. No smokir ion source.

Page 1/8

Revision: 08.02.2021

Printing date 08.02.2021

Revision: 08.02.2021

Trade name: Aerosol PU Wasserlack Klarlack mattiert

(Contd. of page 1)

• Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EUH208 Contains 2-methyl-2H-isothiazol-3-one, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1). May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 115-10-6	dimethyl ether	25-<50%		
EINECS: 204-065-8	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280			
Reg.nr.: 01-2119472128-37-xxxx				
CAS: 64-17-5	ethanol	2.5-<5%		
EINECS: 200-578-6	🚸 Flam. Liq. 2, H225; 🚺 Eye Irrit. 2, H319			
Reg.nr.: 01-2119457610-43-xxxx				
Additional information: For the wording of the listed hazard phrases refer to section 16.				

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

GB

Printing date 08.02.2021

Revision: 08.02.2021

Trade name: Aerosol PU Wasserlack Klarlack mattiert

(Contd. of page 2)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Keep away from heat and direct sunlight.
- · Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material.
- Keep ignition sources away Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm

Long-term value: 766 mg/m³, 400 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

• Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

GB

Printing date 08.02.2021

Revision: 08.02.2021

Trade name: Aerosol PU Wasserlack Klarlack mattiert

(Contd. of page 3) • For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

*

• Eye protection: Not required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:-24.9 °C
Flash point:	<0 °C
-	Without propellant gas.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	235 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive ai
	vapour mixtures are possible.
	Not determined.
Explosion limits:	
Lower:	3 Vol %
Upper:	18.6 Vol %
Vapour pressure at 20 °C:	3400 hPa
Density at 20 °C:	0.897 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	36.7 %
G	With propellant gas. Content given by weight.
Water:	42.9 %
VOC (EU)	36.71 %
	(Contd. on page

Printing date 08.02.2021

Revision: 08.02.2021

(Contd. of page 4)

Trade name: Aerosol PU Wasserlack Klarlack mattiert

Solids content:

19.4 %

• 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- $\cdot \textit{STOT-single exposure Based on available data, the classification criteria are not met.}$
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Printing date 08.02.2021

Revision: 08.02.2021

Trade name: Aerosol PU Wasserlack Klarlack mattiert

(Contd. of page 5)

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
ADR	
· Class	2 5F Gases.
Label	2.1
Class Label 14.4 Packing group ADR, IMDG, IATA	2.1 2.1 Void not classified
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Hazard identification number (Kemler code):	Warning: Gases. - not classified
EMS Number: Stowage Code	F-D,S-U SW1 Protected from sources of heat.
· Segregation Code	SW2 Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 lin Segregation as for class 9. Stow "separated from" cla except for division 1.4. For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
· 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	of Not applicable.

Printing date 08.02.2021

Revision: 08.02.2021

Trade name: Aerosol PU Wasserlack Klarlack mattiert

	(Cont	d. of page
· Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	1L	
\cdot Excepted quantities (\widetilde{EQ})	Code: E0	
	Not permitted as Excepted Quantity	
· Transport category	2	
• Tunnel restriction code	D	
· IMDG		
· Limited quantities (LQ)	1L	
· Excepted quantities ($\widetilde{E}Q$)	Code: E0	
	Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: < 840g/l

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

· Technical instructions (air):

Class	Share in %
Wasser	25-<50
NK	25-<50

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.

- · Department issuing SDS: Product safety department
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

Printing date 08.02.2021

Revision: 08.02.2021

Trade name: Aerosol PU Wasserlack Klarlack mattiert

vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 · * Data compared to the previous version altered. (Contd. of page 7)

GB